
PNEUMATIC TORQUE WRENCH -PNSD SERIES









We have 25 plus years of experience in torque wrench manufacturing. We designed and developed our toolsfor extreme duty use in a diversity of industries worldwide.

Features: -

- · Design for maximize efficiency
- · Wide torque range suits different applications
- · Reliable, dependable solution for the installation and removal for heavy duty fasteners
- · Advanced star-gearbox design basic on reliable quality Precision+/-4%, Repeat Precision+/-2%
- · Reduced operator strain and injury
- · Collectively it will help into increase productivity

Special reaction arm can be ordered according your operation

Model	Square Drive	Torque	Speed RPM	Weight in kg	Noise Level	Dimension IN MM			
						Α	В	С	D
PNSD13	3/4"	275-1350 Nm	15	3.5	80 dBa	207	70	261	31.5
PNSD20	1"	400-2000 Nm	10	3.9	80 dBa	201	70	261	34.5
PNSD34	1"	700-3400 Nm	4.8	7.0	85 dBa	269	89	272	38.5
PNSD80	1-1/2"	2700-8000 Nm	4.2	12.2	85 dBa	317	93	293	51

*Max Air consumption is 10-90 psi / Flow 45-55 CFM

Precision+/-4%, Repeat Precision+/-2%



Standard Accessories:

- ·Reaction Arm
- · Lock Circlip
- · Air Hose 8 ft
- · Air Gauge, Filter, Regulator
- ·Carry Case
- · Air-Torque Chart

Part No: PNSD FRL-1Operating Manual